

MATERIAL LIST - STANDARD UNIT	
ITEM	DESCRIPTION
1	POWER DESIGN INC MODEL NO CJP-15/B FIBERGLASS CABLE JUNCTION PEDESTAL - MUNSELL GREEN
2	ALUMINUM JUNCTION MOUNTING BAR AND PARKING CLIP MOUNTING RAILS
3	ADJUSTABLE LOCATION STAINLESS STEEL PARKING CLIPS

OPTIONAL EQUIPMENT	
51	600 AMP DEADBREAK JUNCTION - 15KV OR 25KV - 95/125KV BIL - SPECIFY VOLTAGE, MANUFACTURER AND 2, 3 OR 4-WAY

ORDERING INFORMATION:
 USER SHOULD SELECT 'D', BURIAL DEPTH, DESIRED.
 SPECIFY 'A', OVERALL HEIGHT, AS A SUFFIX TO THE BASIC PART NO.
 i.e.; CJP-15/B-49 = 49' OVERALL HEIGHT
 15.1/2" TERMINAL HEIGHT MAY BE INCREASED BY DECREASING BURIAL DEPTH OR ORDERING THE NEXT SIZE GREATER 'A' DIMENSION.


- NOTE:**
- MATERIAL:**
 - FIBERGLASS LAMINATE 3/16" NOMINAL THICKNESS
 - EXTERIOR UV STABILIZED GELCOAT - 14 MIL NOMINAL THICKNESS - WHITE INTERIOR
 - FIRE RETARDANT - DOES NOT SUPPORT COMBUSTION
 - STAINLESS STEEL HARDWARE
 - MOUNTING BAR WILL WITHSTAND A MINIMUM 400 LB. LOADING TO INSTALL OR REMOVE ELBOWS.

MODEL No.	OVERALL HEIGHT	OVERALL WIDTH AT BOTTOM	OVERALL DEPTH AT BOTTOM	MAXIMUM RECOMMENDED BURIAL DEPTH SEE NOTE 1
	A	B	C	D
CJP-15/B-33	33'	54.1/2'	40.1/4'	12"
CJP-15/B-39	39'	55.1/4'	41'	18"
CJP-15/B-49	49'	57.1/4'	43'	28"
CJP-15/B-54	54'	58.3/4'	44.1/2'	33"

DEADFRONT CABLE JUNCTION PEDESTAL
 15/25KV 600 AMP 95/125KV BIL
 TWO PHASE 2, 3 OR 4-WAY DEADBREAK JUNCTION

POWER DESIGN INC.
 ODELL, OREGON

DRAWN: RB	PAGE	DATE: 3-29-04	DRAWING NO: 3318-R1
-----------	------	---------------	---------------------



SCHEMATIC

FILE REF: