



PAD & ANCHOR BOLT DETAIL
 ANCHOR BOLTS TO BE 5/8" DIA. AND TO EXTEND 1-1/2" MINIMUM ABOVE PAD
 PROVIDE UTILITY ENTRY AS REQUIRED

ORDERING INFORMATION:

MODEL _____ ME 3 - 72 - 3438 - L2 - LG _____ COLOR _____

NUMBER OF DOORS _____

NOMINAL WIDTH _____

DETAILS AS SHOWN ON THIS DRAWING _____

NOTE:

1. MATERIAL:

- 1) FIBERGLASS LAMINATE 1/4" NOMINAL THICKNESS
- 2) EXTERIOR UV STABILIZED GELCOAT - 14 MIL NOMINAL THICKNESS
- 3) FIRE RETARDANT - DOES NOT SUPPORT COMBUSTION
- 4) STAINLESS STEEL HARDWARE

2. STANDARDS:

- 1) CERTIFIED TEST DATA OF ASTM STRUCTURAL STANDARDS AVAILABLE UPON REQUEST

LG - LIGHT GRAY
 WG - LIGHT GREEN
 MG - MUNSELL GREEN
 OTHER COLORS AVAIL. CONSULT FACTORY

L1 - PROVISION FOR PADLOCKING ONLY
 L2 - PROVISION FOR PADLOCKING & PENTA HEAD BOLT
 L4 - PROVISION FOR PADLOCKING, PENTA HEAD BOLT & INNER DOORS

FIBERGLASS MODULAR ENCLOSURE
 6 FT WIDE x 8 FT 9 IN HIGH x 14 FT LONG
 ONE DOUBLE & ONE SINGLE DOOR BRKR BOX, LIGHTS, RECEPTACLE

POWER DESIGN INC.
 ODELL, OREGON

DRAWN: BB	PAGE	DATE 4-4-03	DRAWING NO. 3438
--------------	------	----------------	---------------------

FILE REF: