


MATERIAL LIST - STANDARD UNIT			
ITEM	DESCRIPTION		
1	POWER DESIGN INC MODEL NO CJP-41-56-L2-MG FIBERGLASS CABLE JUNCTION PEDESTAL - MUNSELL GREEN		
2	ALUMINUM JUNCTION MOUNTING BAR AND PARKING CLIP MOUNTING RAILS		
3	ADJUSTABLE LOCATION STAINLESS STEEL PARKING CLIPS		
4	18" FIBERGLASS SUB-BASE MODEL NO CJP-41-18-MB-MG		
OPTIONAL EQUIPMENT			
51	600 AMP DEADBREAK JUNCTION - 35KV - 150KV BIL - COOPER JUNCTIONS 2, 3 OR 4-WAY		
52	3/8" GROUND BAR		
53	STAINLESS STEEL UNISTRUT FOR CABLE SUPPORT - REMOVED FOR SHIPPING		
NOTE:			
1. MATERIAL:			
1) FIBERGLASS LAMINATE 3/16" NOMINAL THICKNESS			
2) EXTERIOR UV STABILIZED GELCOAT - 14 MIL NOMINAL THICKNESS - WHITE INTERIOR			
3) FIRE RETARDANT - DOES NOT SUPPORT COMBUSTION			
4) STAINLESS STEEL HARDWARE			
2. MOUNTING BAR WILL WITHSTAND A MINIMUM 400 L.B. LOADING TO INSTALL OR REMOVE ELBOWS.			
3. CATALOG NO WITH OPTIONS: CJP-41-56-L2-MG-6435-GB38-CS-3398-R1			
CATALOG NO: CJP-41-56-L2-MG-3398-R1			
DEADFRONT CABLE JUNCTION PEDESTAL			
35KV      600 AMP      150KV BIL			
THREE PHASE      2, 3 OR 4-WAY COOPER JUNCTION			
 <b>POWER DESIGN INC.</b> ODELL, OREGON			
DRAWN: RB	PAGE	DATE 9-17-08	DRAWING NO. 3398-R1

FILE REF: